

HOW UNCONDITIONALLY SECURE QUANTUM BIT COMMITMENT IS POSSIBLE

Horace P. Yuen

Department of Electrical and Computer Engineering

Department of Physics and Astronomy

Northwestern University

Evanston IL 60208-3118

email: yuen@ece.northwestern.edu

Abstract

Bit commitment involves the submission of evidence from one party to another so that the evidence can be used to confirm a later revealed bit value by the first party, while the second party cannot determine the bit value from the evidence alone. It is widely believed that unconditionally secure quantum bit commitment is impossible due to quantum entanglement cheating, which is codified in a general impossibility theorem. In this paper, the scope of this general impossibility proof is analyzed, and gaps are found. Two variants of a bit commitment scheme utilizing anonymous quantum states and decoy states are presented. In the first variant, the exact verifying measurement is independent of the committed bit value, thus the second party can make it before the first party opens, making possible an unconditional security proof based on no-cloning. In the second variant, the impossibility proof fails because quantum entanglement purification of a mixed state does not render the protocol determinate. Whether impossibility holds in this or similar protocols is an open question, although preliminary results already show that the impossibility proof cannot work as it stands.

PACS #: 03.67Dd, 03.65Bz

Note:

We have made a few clarifications and elaborations in this revision.

Contents

I	Introduction	3
II	The Impossibility Proof	6
III	The Impossibility Proof and Anonymous States	12
IV	Bit Commitment Scheme that Contradicts the Impossibility Proof	18
	Protocol QBCp3m	20
	Protocol QBCp3u	24
V	Unconditionally Secure Bit Commitment Schemes	25
	Protocol QBC3m1	26
	Protocol QBC3m2	27
VI	Conclusion	29
	Acknowledgment	30
	Appendix A: Proof of Theorem 2	31
	Appendix B: Example on Proper Concealing	32
	Appendix C: Evaluation of Trace Distance	33
	Appendix D: Simple Summary of Protocols QBCp3m, etc.	34
	References	35

I Introduction

Quantum cryptography [1], the study of information security systems involving quantum effects, has recently been associated almost exclusively with the cryptographic objective of key distribution. This is due primarily to the nearly universal acceptance of the general impossibility of secure quantum bit commitment (QBC), taken to be a consequence of the Einstein-Podolsky-Rosen (EPR) type entanglement cheating which rules out QBC and other quantum protocols that have been proposed for various other cryptographic objectives [2]. In a bit commitment scheme, one party, Adam, provides another party, Babe, with a piece of evidence that he has chosen a bit b (0 or 1) which is committed to her. Later, Adam would “open” the commitment: revealing the bit b to Babe and convincing her that it is indeed the committed bit with the evidence in her possession. The usual concrete example is for Adam to write down the bit on a piece of paper which is then locked in a safe to be given to Babe, while keeping for himself the safe key that can be presented later to open the commitment. The evidence should be *binding*, i.e., Adam should not be able to change it, and hence the bit, after it is given to Babe. It should also be *concealing*, i.e., Babe should not be able to tell from it what the bit b is. Otherwise, either Adam or Babe would be able to cheat successfully.

In standard cryptography, secure bit commitment is to be achieved either through a trusted third party or by invoking an unproved assumption on the complexity of certain computational problem. By utilizing quantum effects, various QBC schemes not involving a third party have been proposed that were supposed to be unconditionally secure, in the sense that neither Adam nor Babe can cheat with any significant probability of success as a matter of physical laws. In 1995-1996, a general proof on the impossibility of unconditionally secure QBC and the insecurity of previously proposed protocols were described [3]-[5]. Henceforth, it has been generally accepted that secure QBC and related objectives are impossible as a matter of principle [6]-[10].

There is basically just one impossibility proof, which gives the EPR attacks for the cases of equal and unequal density operators that Babe has for the two different bit values. The proof shows that if Babe’s successful cheating probability P_c^B is close to the value $1/2$, which is

obtainable from pure guessing of the bit value, then Adam’s successful cheating probability P_c^A is close to the perfect value 1. This result is stronger than the mere impossibility of unconditional security, namely that it is impossible to have both $P_c^B \sim 1/2$ and $P_c^A \sim 0$. Since there is no known characterization of all possible QBC protocols, logically there can really be no general impossibility proof even if it were indeed impossible to have an unconditionally secure QBC protocol.

In this paper, the formulation within which the general impossibility proof was developed will be analyzed. The mechanism for the success of the impossibility proof within a limited scope will be delineated. It is shown that the use of classical randomness unknown to one of the two parties, common in many standard cryptographic protocols, is not properly accounted for in the previous impossibility proof formulation. In particular, the turning of classical randomness into quantum determinateness via quantum purification of a mixed quantum state does *not* render a quantum protocol determinate with no further role for classical randomness, as described in the impossibility proof. Specifically, a scheme utilizing anonymous states and decoy states will be presented, and the different ways in which the impossibility proof fails for these variants will be explicitly pinpointed. The results are developed within nonrelativistic quantum mechanics, unrelated to relativistic protocols [11] or cheat-sensitive protocols [12]. Since bit commitment leads to “coin-tossing” and other cryptographic protocols, our present results have immediate impact on many recent works on quantum coin-tossing and multiparty computation.

To provide a foretaste of the failure of the impossibility proof, the following two points may be mentioned. First, the impossibility proof has *no* role for any possible classical randomness that Babe may introduce, which, even after quantum purification, would actually be explicitly used by her in her verification of the bit. If the use of such randomness by Babe is taken into account, it is not hard to see that the success of Adam’s EPR cheat may depend on knowing the actual value of such random numbers. Secondly, there are concealing protocols for which Babe can make all the measurements for verification *before* Adam opens because the verifying measurement is independent of the bit value, with no consequent possibility that an information carrying state needs to be discarded due to measurement basis mismatch. This kind of protocol is one of several types outside the impossibility proof formulation.

Indeed, a general formulation of all possible QBC protocols is not yet available that includes a proper expression of just the concealing condition, not to mention both concealing and binding with corresponding expressions for the cheating probabilities.

In section II, the impossibility proof would be described and extended. The mechanism of its success within its limited scope will be highlighted. In section III, the use of anonymous states in QBC will be developed, in which Babe uses classical random numbers in the most direct way in protocols involving two-way quantum communication. It is explicitly demonstrated that the impossibility proof, specifically the use of the doctrine “Church of Larger Hilbert Space,” fails to cover such situations in two different ways. In section IV, our basic scheme is introduced in a preliminary form which is not yet unconditionally secure but which already invalidates the impossibility proof. Two variants of the scheme are described. One of which, QBCp3m, allows Babe to make perfect verifying measurements before Adam opens. The reader is urged to first read Appendix D for a concise presentation of this basically rather simple protocol, as it confirms our statement above that there can be no general impossibility proof without a characterization of all possible QBC protocols. In section V, the protocol QBCp3m is extended to fully unconditionally secure ones together with their security proofs. Some general and practical observations are made in the last section VI. Note that the same index may denote different quantities in different sections, and the notation $\otimes$ is often omitted for brevity.

II The Impossibility Proof

In this Section we review the standard formulation of the impossibility proof, present some pertinent new results, and explain the precise mechanism of the EPR cheating.

According to the impossibility proof, Adam would generate $|\Phi_0\rangle$ or $|\Phi_1\rangle$ depending on $b = 0$ or 1 ,

$$|\Phi_0\rangle = \sum_i \sqrt{p_i} |e_i\rangle |\phi_i\rangle, \quad (1)$$

$$|\Phi_1\rangle = \sum_i \sqrt{p'_i} |e'_i\rangle |\phi'_i\rangle \quad (2)$$

where the states $\{|\phi_i\rangle\}$ and $\{|\phi'_i\rangle\}$ in $\mathcal{H}^B$ are openly known, $i \in \{1, \dots, M\}$, $\{p_i\}$ and $\{p'_i\}$ are known probabilities, while $\{|e_i\rangle\}$ and $\{|e'_i\rangle\}$ are two complete orthonormal sets in $\mathcal{H}^A$. All Dirac kets are normalized in this paper. Adam sends Babe $\mathcal{H}^B$ while keeping $\mathcal{H}^A$ to himself. He opens by measuring the basis $\{|e_i\rangle\}$ or $\{|e'_i\rangle\}$ in $\mathcal{H}^A$ according to his committed state $|\Phi_0\rangle$ or $|\Phi_1\rangle$, resulting in a specific $|\phi_i\rangle$ or $|\phi'_i\rangle$ on $\mathcal{H}^B$, and telling Babe which i he has obtained. Babe verifies by measuring the corresponding projector and will obtain the value 1 (yes) with probability 1. In this formulation, Adam can switch between $|\Phi_0\rangle$ and $|\Phi_1\rangle$ by operation on $\mathcal{H}^A$ alone, and thus alter the evidence to suit his choice of b before opening the commitment. In the case $\rho_0^B \equiv \text{tr}_A |\Phi_0\rangle\langle\Phi_0| = \rho_1^B \equiv \text{tr}_A |\Phi_1\rangle\langle\Phi_1|$, the switching operation is to be obtained by using the so-called ‘‘Schmidt decomposition [13],’’ the expansion of $|\Phi_0\rangle$ and $|\Phi_1\rangle$ in terms of the eigenstates $|\hat{\phi}_k\rangle$ of $\rho_0^B = \rho_1^B$ with eigenvalues λ_k and the eigenstates $|\hat{e}_k\rangle$ and $|\hat{e}'_k\rangle$ of ρ_0^A and ρ_1^A ,

$$|\Phi_0\rangle = \sum_k \sqrt{\lambda_k} |\hat{e}_k\rangle |\hat{\phi}_k\rangle, \quad |\Phi_1\rangle = \sum_k \sqrt{\lambda_k} |\hat{e}'_k\rangle |\hat{\phi}_k\rangle \quad (3)$$

By applying a unitary U^A that brings $\{|\hat{e}_k\rangle\}$ to $\{|\hat{e}'_k\rangle\}$, Adam can select between $|\Phi_0\rangle$ or $|\Phi_1\rangle$ any time before he opens the commitment but after he supposedly commits. When ρ_0^B and ρ_1^B are not equal but close, it was shown that one may transform $|\Phi_0\rangle$ by an U^A to a $|\tilde{\Phi}_0\rangle$ with $|\langle\Phi_1|\tilde{\Phi}_0\rangle|$ as close to 1 as ρ_0^B is close to ρ_1^B according to the fidelity F chosen, and thus the state $|\tilde{\Phi}_0\rangle$ would serve as the effective EPR cheat.

In addition to the above quantitative relations, the gist of the impossibility proof is supposed to lie in its generality – that any QBC protocol could be fitted into its formulation,

as a consequence of various arguments advanced in [3]-[10]. Among other reasons, it appeared to the present author from his development of a new cryptographic tool, anonymous quantum key technique [14], that the impossibility proof is not sufficiently general. Since there is no need for Adam to entangle anything in an honest protocol. Adam can just send Babe a state $|\phi_i\rangle$ with probability p_i when he picks $b=0$. When he picks $b=1$, he sends $|\phi'_i\rangle$ with probability p'_i . If the anonymous key technique is employed, $|\phi_i\rangle$ and $|\phi'_i\rangle$ are to be obtained from applying U_{0i} or U_{1i} from some fixed openly known set of unitary operators $\{U_{0i}\}$ and $\{U_{1i}\}$ on $\mathcal{H}^B$ by Adam to the states $|\psi\rangle$ sent to him by Babe and known only to her. As a consequence, Adam would not be able to determine the cheating unitary transformation U^A . This use of anonymous states is *not* explicitly accounted for in the open literature, and the role of classical random numbers in the problem formulation is not clearly and fully laid out in the impossibility proof. However, it seems the prevailing opinion is that the impossibility proof covers classical randomness in essence, basically through the use of quantum purification of classical randomness [4], [7], [15]. This claim that the impossibility proof covers all classical randomness has never been explicitly demonstrated, and it is one major purpose of this paper to show that such a claim is erroneous. The gap in the reasoning, to be delineated in section III, is best appreciated after a careful quantitative development of the impossibility proof to be presently given.

In a QBC protocol, the $\{|\phi_i\rangle\}$ and $\{|\phi'_i\rangle\}$ are chosen so that they are concealing as evidence, i.e. Babe cannot reliably distinguish them in optimum binary hypothesis testing [16]. They would also be binding if Adam is honest and sends them as they are above, which he could not change after Babe receives them. Babe can always guess the bit with a probability of success $P_c^B = 1/2$, while Adam should not be able to change a committed bit at all. However, it is meaningful and common to grant *unconditional security* when the best $\bar{P}_c^B$ Babe can achieve is arbitrarily close to $1/2$ and Adam's best probability of successfully changing a committed bit $\bar{P}_c^A$ is arbitrarily close to zero even when both parties have perfect technology and unlimited resources including unlimited computational power [4].

The operation of unitary transformation with subsequent measurement of an orthonormal basis is equivalent to the mere measurement of another orthonormal basis $\{|\tilde{e}_i\rangle\}$ on the

system. Thus, the net cheating operation can be described by writing

$$|\Phi_0\rangle = \sum_i \sqrt{\tilde{p}_i} |\tilde{e}_i\rangle |\tilde{\phi}_i\rangle, \quad (4)$$

$$\sqrt{\tilde{p}_i} |\tilde{\phi}_i\rangle \equiv \sum_j \sqrt{p_j} V_{ji} |\phi_j\rangle \quad (5)$$

for a unitary matrix V defined by $|e_i\rangle = \sum_j V_{ij} |\tilde{e}_j\rangle$, and then measuring $|\tilde{e}_i\rangle$. For convenience, we may still in the rest of the paper refer to the cheating operation as a U^A transformation described at the beginning of this Section, with $|e_i\rangle = U^A |\tilde{e}_i\rangle$. From (5), the $|\tilde{\phi}_i\rangle$ obtainable by operation on $\mathcal{H}^A$ alone are some unitary linear combinations of the $|\phi_i\rangle$. The quantitative expression for P_c^A can now be given. If Babe verifies the individual $|\phi'_i\rangle$, the Adam's successful cheating probability is

$$P_c^A = \sum_i \tilde{p}_i |\langle \tilde{\phi}_i | \phi'_i \rangle|^2. \quad (6)$$

When randomness from Babe is present, further averaging is needed to yield the final P_c^A . The EPR cheating mechanism is clear from (5)—via entanglement and measurement of a different basis, Adam can generate *unitary linear combinations of the committed states* $|\phi_i\rangle$ to approximate the states $|\phi'_i\rangle$. The approximation is guaranteed to be good when the protocol is concealing, as follows.

In general, the optimal cheating probability $\bar{P}_c^B$ for Babe is given by the probability of correct decision for optimally discriminating between two density operators ρ_0^B and ρ_1^B by any quantum measurement. For equal a priori probabilities,

$$\bar{P}_c^B = \frac{1}{4}(2 + \|\rho_0^B - \rho_1^B\|_1) \quad (7)$$

where $\|\cdot\|_1$ is the trace norm, $\|\tau\|_1 \equiv \text{tr}(\tau^\dagger \tau)^{1/2}$, for a trace-class operator τ [17]. In terms of a security parameter n that can be made arbitrarily large, the statement of unconditional security (US) can be quantitatively expressed as

$$(\text{US}) \quad \lim_n \bar{P}_c^B = \frac{1}{2} \quad \text{and} \quad \lim_n \bar{P}_c^A = 0. \quad (8)$$

Condition (US) is equivalent to the statement that for any $\epsilon > 0$, there exists an n_0 such that for all $n > n_0$, $\bar{P}_c^B - \frac{1}{2} < \epsilon$ and $\bar{P}_c^A < \epsilon$, i.e. $\bar{P}_c^B - \frac{1}{2}$ and $\bar{P}_c^A$ can both be made

arbitrarily small for sufficiently large n . The impossibility proof claims more than the mere impossibility of (US), it asserts [3] the following statement (IP):

$$(IP) \quad \bar{P}_c^B = \frac{1}{2} + O\left(\frac{1}{n}\right) \Rightarrow \bar{P}_c^A = 1 - O\left(\frac{1}{n}\right) \quad (9)$$

Condition (9) implies the following limiting statement

$$(IP') \quad \lim_n \bar{P}_c^B = \frac{1}{2} \Rightarrow \lim_n \bar{P}_c^A = 1. \quad (10)$$

that directly contradicts (8). One may regard (IP') as the general impossibility statement, independently of the specific convergence rate of (9). In the $\rho_0^B = \rho_1^B$ case, the EPR cheat shows that $\bar{P}_c^B = \frac{1}{2}$ implies $\bar{P}_c^A = 1$. Thus (IP') generalizes it to the assertion that the function $\bar{P}_c^A(\bar{P}_c^B)$, obtained by varying n , is *continuous* from above at $\bar{P}_c^B = \frac{1}{2}$. Note the difference between the truth of (IP') and the weaker statement that (US) is impossible. In the middle ground that $\lim_n \bar{P}_c^B = \frac{1}{2}$ implies just $0 < \lim_n \bar{P}_c^A < 1$, the protocol would be concealing for Babe and quantitatively cheat-sensitive for Adam. However, it may be expected that if $\bar{P}_c^A$ is not close to 1, it may be made close to 0 in an extension protocol which thus becomes unconditionally secure.

The cheating transformation for the $\rho_0^B \neq \rho_1^B$ case is determined from ref. [18] according to the impossibility proof [3]-[4], which would proceed as follows. Let $|\lambda_i\rangle$ and $|\mu_i\rangle$ be the eigenstates of ρ_0^B and ρ_1^B with eigenvalues λ_i and μ_i . The Schmidt normal forms of the purifications $|\Phi_0\rangle$ and $|\Phi_1\rangle$ of ρ_0^B and ρ_1^B are given by

$$|\Phi_0\rangle = \sum_i \sqrt{\lambda_i} |f_i\rangle |\lambda_i\rangle, \quad (11)$$

$$|\Phi_1\rangle = \sum_i \sqrt{\mu_i} |g_i\rangle |\mu_i\rangle \quad (12)$$

for complete orthonormal sets $\{|f_i\rangle\}$ and $\{|g_i\rangle\}$ on $\mathcal{H}^A$. Define the unitary operators U_0 , U_1 and U_2 by

$$U_0 |\lambda_i\rangle = |\mu_i\rangle, \quad (13)$$

$$U_1 |\lambda_i\rangle = |f_i\rangle, \quad (14)$$

$$U_2 |\mu_i\rangle = |g_i\rangle. \quad (15)$$

Let U be the unitary operator for the polar decomposition of $\sqrt{\rho_0^B}\sqrt{\rho_1^B}$,

$$\sqrt{\rho_0^B}\sqrt{\rho_1^B} = \left| \sqrt{\rho_0^B}\sqrt{\rho_1^B} \right| U. \quad (16)$$

Then $|\langle \Phi_0 | \Phi_1 \rangle|$ assumes its maximum value $F(\rho_0^B, \rho_1^B)$, $F(\rho_0, \rho_1) \equiv \text{tr} \sqrt{\sqrt{\rho_0} \rho_1 \sqrt{\rho_0}}$, when

$$UU_2^T U_0 U_0^T U_1^{T\dagger} = I \quad (17)$$

where T denotes the transpose operation. Thus, when ρ_0^B, ρ_1^B , and $|e_i\rangle$ are given, $|g_i\rangle = |e'_i\rangle$ of $|\Phi_1\rangle$ is determined from (12) via solving for U_2 from (17). In general, these U 's are isometries, but the above relations still hold.

The above formulation (11)-(17), utilizing Jozsa's proof [18] of Uhlmann's theorem, covers both the $\rho_0^B = \rho_1^B$ case and the $U^A = I$ (i.e., $|\Phi_0\rangle = |\Phi_1\rangle$) situation as special cases. Apparently from these equations, knowledge of the eigenstates of ρ_0^B and ρ_1^B is required to find the cheating transformation U^A that brings $|e_i\rangle$ to $|\tilde{e}_i\rangle$. Actually, both (11)-(17) and the Schmitt decomposition obscure the underlying mechanism of the EPR cheating given by (5). In the present context, they suggest that knowledge of the ρ_b^B eigenstates is needed to determine U^A , which is actually much simpler determined by the following

Theorem 2:

The U^A that maximizes $|\langle \tilde{\Phi}_0 | \Phi_1 \rangle|$, defined through the matrix $\mathbf{U}, U_{ij} \equiv \langle e_i | U^A | e_j \rangle$, is determined by

$$\mathbf{\Lambda} \mathbf{U} = |\mathbf{\Lambda}| \quad (18)$$

where

$$\Lambda_{ij} \equiv \sqrt{p'_i p_j} \langle \phi'_i | \phi_j \rangle, \quad |\mathbf{\Lambda}| \equiv (\mathbf{\Lambda} \mathbf{\Lambda}^\dagger)^{\frac{1}{2}} \quad (19)$$

When $p_i = p'_i$, the corresponding

$$\tilde{P}_c^A = \sum_i (|\mathbf{\Lambda}|_{ii})^2 \quad (20)$$

which satisfies

$$F^2 \leq \tilde{P}_c^A \leq F \quad (21)$$

The lower bound in (21) is valid also for $p_i \neq p'_i$.

Theorem 2 is proved in Appendix A. Note that in terms of the $\mathbf{V}$ in (5), $\mathbf{U} = \mathbf{V}^T$. The bounds (21) simply characterize $\tilde{P}_c^A$ in terms of F , and yield $\bar{P}_c^A \geq F^2$ for the actual optimal probability $\bar{P}_c^A$ that maximizes (6). This lower bound yields the usual impossibility proof [3] or (IP) of (9) when combined with the lower bound on $\|\cdot\|_1$ in terms of F [19]. When $\mathbf{\Lambda}$ is invertible, $\mathbf{U} = \mathbf{\Lambda}^{-1}|\mathbf{\Lambda}|$ from (18). In general, one does not need to compute the eigenstates of ρ_b^B to find U^A , which is determined through $\mathbf{\Lambda}$ that is given directly in terms of the known states and probabilities.

III The Impossibility Proof and Anonymous States

The use of anonymous states by Babe as briefly described in the last section is just one obvious way to introduce classical randomness for her in a QBC protocol, which appears to thwart Adam's EPR cheating by denying him the knowledge to find the proper cheating transformation. The ways in which the impossibility proof fails in this situation are detailed in this section.

In general, such use of anonymous states by Babe can be described as follows. She sends Adam a state $|\psi\rangle \in \mathcal{H}^{\mathcal{B}}$ known only to herself. Depending on $b = 0$ or 1 , Adam applied to $|\psi\rangle$ a unitary operator $U_{bi}, i \in \{1, \dots, M\}$ with probabilities p_i or p'_i . In the notation of section II,

$$|\phi_i\rangle = U_{0i}|\psi\rangle, \quad |\phi'_i\rangle = U_{1i}|\psi\rangle \quad (22)$$

Adam sends the modulated state back to Babe, and opens by revealing b and i . He can form the entangled $|\Phi_0\rangle$ by applying the unitary operator U_0 on $\mathcal{H}^{\mathcal{A}} \otimes \mathcal{H}^{\mathcal{B}}$,

$$U_0 = \sum_i |e_i\rangle\langle e_i| \otimes U_{0i} \quad (23)$$

with initial state $|A\rangle \in \mathcal{H}^{\mathcal{A}}$ satisfying $\langle e_i|A\rangle = \sqrt{p_i}$. It appears from Theorem 2 above that the cheating transformation U^A as determined by $\langle \phi'_i|\phi_j\rangle = \langle \psi|U_{1i}^\dagger U_{0j}|\psi\rangle$ would depend on $|\psi\rangle$ in general, thus cannot be found by Adam. The impossibility proof handles this situation rather explicitly in [4], [6], [10], and [15], in the following way.

The state $|\psi\rangle$ is supposed to be picked by Babe from a set $\{|\psi_k\rangle\}, k \in \{1, \dots, L\}$ with probabilities λ_k that are all openly known. The associated classical randomness is then purified by having Babe generate the entangled state

$$|\Psi\rangle = \sum_k \sqrt{\lambda_k} |\psi_k\rangle |f_k\rangle, \quad (24)$$

where the $|f_k\rangle$'s are complete orthonormal in $\mathcal{H}^{\mathcal{C}}$, send $\mathcal{H}^{\mathcal{B}}$ to Adam while keeping $\mathcal{H}^{\mathcal{C}}$ to herself. At the end of the commitment phase she would measure $\{|f_k\rangle\}$ to pin down a specific $|\psi_k\rangle$. The proof, however, is *not* carried to the end, and the above description is considered sufficient to ensure that the impossibility proof works in the presence of classical randomness introduced by Babe—from quantum entanglement purification of a mixed state

and postponement of all measurements to end of commitment, the classical randomness is rendered quantum-mechanically determinate and everything is known to Adam again for him to find the cheating transformation U^A . While Babe may not actually form $|\Psi\rangle$, the so-called “Church of Larger Hilbert Space” doctrine [20] is used to justify the equivalence. In the following, it will be shown that the equivalence does not hold when Babe does something else to cheat, and that the impossibility proof does not go through even when Babe actually forms $|\Psi\rangle$ and postpone her measurement on $\mathcal{H}^C$ until after Adam opens.

To spell out the impossibility proof argument, one actually needs to show that U^A is independent of $\{|f_k\rangle\}$ in $\mathcal{H}^C$ and Adam only needs $\mathcal{H}^B$, not the full $|\Psi\rangle$ of (24), to form his entanglement. These turn out to be true as a consequence of (18) in Theorem 2 above. However, it is against common probabilistic intuition that randomness would altogether disappear (to Adam) upon a quantum interpretation. There is no reason why Babe has to generate (24) instead of any specific $|\psi_k\rangle$. More generally, to form $|\Psi\rangle$, Babe can choose any probability distribution on $\{|\psi_k\rangle\}$, not the $\{\lambda_k\}$ that Adam believes. It is not a meaningful formulation to assume that Adam knows $\{\lambda_k\}$. Thus, one *cannot* eliminate via quantum purification what is nonrandom to Babe (upon her choice or measurement) and random to Adam [21]. Indeed, Babe can generate any state $|\psi\rangle \in \mathcal{H}^B$, or any entangled state $|\Phi\rangle \in \mathcal{H}^B \otimes \mathcal{H}^C$ for any $\mathcal{H}^C$ that she keeps to herself. A careful formulation for the concealing condition needs to be developed.

To show the inadequacy of the formulation of the impossibility proof, assume that $\rho_0^B(\Psi)$ and $\rho_1^B(\Psi)$ are indeed close from the use of (22) and (24) with $\lambda_k = 1/L$ for L large. Let $|\psi_1\rangle$ be such that $\rho_0^B(\psi_1)$ and $\rho_1^B(\psi_1)$ are far apart, being possible even though $\rho_0^B(\Psi)$ and $\rho_1^B(\Psi)$ are close because $1/L$ is small. Then Babe can cheat by using $\lambda_1 = 1$ instead of $\lambda_k = 1/L$. To ensure a concealing protocol, one must impose the uniformity condition

$$\rho_0^B(\psi) \approx \rho_1^B(\psi), \quad \forall \psi \in \mathcal{H}^B, \quad (25)$$

or, more generally,

$$\rho_0^{BC}(\Psi) \approx \rho_1^{BC}(\Psi), \quad \forall \Psi \in \mathcal{H}^B \otimes \mathcal{H}^C \quad (26)$$

for any $\mathcal{H}^C$ Babe can use to entangle, with $\approx$ being taken in the sense of trace norm from (7). Such a concealing condition has not been given in the literature, but it is needed whenever

a state is passed from Babe to Adam in a proper formulation of the problem. From the condition $\rho_0^{BC}(\Psi) \approx \rho_1^{BC}(\Psi)$ for a fixed Ψ , one may at best conclude that $\rho_0^B(\psi_k) \approx \rho_1^B(\psi_k)$ for those k where $\lambda_k \not\approx 0$. Thus, the impossibility proof *errs* in asserting that Adam can cheat under the above condition—he cannot, and Babe can instead. In Appendix B, an example is given in which $\rho_0^{BC}(\Psi) = \rho_1^{BC}(\Psi)$ for a given Ψ , but Adam cannot cheat even when no λ_k is small.

Assuming that condition (25) is satisfied, let us examine how Adam’s EPR cheating works. If one follows the impossibility proof, it would work if Babe verifies on the state $|\Psi\rangle$ of (24), i.e., depending on $b = 0$ or 1 she checks whether $|\Psi\rangle$ becomes

$$U_{bi}|\Psi\rangle = \sum_k \sqrt{\lambda_k} U_{bi}|\psi_k\rangle|f_k\rangle \quad (27)$$

for the i opened by Adam. However, that is *not* the way she verifies according to the protocol. She would make a preliminary measurement of $\{|f_k\rangle\}$ first with result j and then check whether the state is $U_{bi}|\psi_j\rangle$. She can in fact postpone her measurement on $\mathcal{H}^C$ until after Adam opens. The important point is that she is going to make a measurement and use the result in the verification. While such measurement does not allow her to cheat any better, it may help defeat Adam’s EPR cheating. In the impossibility proof there is *no* role given to any classical randomness other than $\{p_i\}$ and $\{p'_i\}$ —it is implicitly assumed that Babe’s random number known only to herself is *not* used in her verification as just described. Such lack of utilization of possible classical randomness represents a huge gap in the impossibility proof, making it severely limited in scope and *incorrect* as a general proof. The doctrine of the “Church of Larger Hilbert Space” is *irrelevant* to the protocol behavior as it should be; it would not make the protocol determinate. It is clear that classical random numbers can be generated by both Adam and Babe in a general quantum protocol, which are kept secret from the other party and used in an essential way as in many standard cryptographic protocols. The impossibility proof does not begin to incorporate such possibilities.

We examine more exactly how the impossibility proof fails in the present situation. The cheating transformation U^A is taken to be the one that maximizes $|\langle\Phi_1|U^A|\Phi_0\rangle|$, not the one that maximizes P_c^A of (6). However, in addition to the lower bound in (21) that applies also to $\bar{P}_c^A$, in general U^A is determined by the inner product matrix $\langle\phi'_i|\phi_j\rangle$, apart from the

a priori probabilities. Any such cheating $\mathbf{U}$ is thus determined via $\sum_k \lambda_k \langle \psi_k | U_{1i}^\dagger U_{0j} | \psi_k \rangle \equiv \bar{u}_{ij}$ for $|\Psi\rangle$, but via $\langle \psi_k | U_{1i}^\dagger U_{0j} | \psi_k \rangle \equiv u_{ij}^k$ for each $|\psi_k\rangle$. There is no reason to expect that the $\mathbf{U}$ as determined by $\bar{u}_{ij}$ would be close to the $\mathbf{U}$ determined by u_{ij}^k , whatever the λ_k 's are.

Actually, one does not need to transform among the maximizing $\mathbf{U}$ in order for impossibility to hold. The general problem can be cast as follows. From (22) and (5), we have dependence of the committed and cheating states on the anonymous state $|\psi\rangle$, to be simply denoted by $\phi_i(\psi)$, $\phi'_i(\psi)$, and $\tilde{\phi}_i(\psi)$ for notational simplicity dropping the Dirac kets, as already done occasionally above. In the present formulation with only anonymous states from Babe in the form (22), all of Adam's possible attacks are described by local measurements and announcing a different b . For this attack to succeed with $\bar{P}_c^A \sim 1$ given $|\Phi_0\rangle$ is committed, one presumably wants

$$\tilde{\phi}_i(\psi) \approx \phi'_i(\psi), \quad \forall \psi \in \mathcal{H}^B \quad (28)$$

or

$$\tilde{\phi}_i(\Psi) \approx \phi'_i(\Psi), \quad \forall \Psi \in \mathcal{H}^B \otimes \mathcal{H}^C \quad (29)$$

for some fixed U^A or $\mathbf{V}$ independent of ψ , the $\approx$ in (28)-(29) taken in the sense of state inner product. Condition (28) expresses the requirement that as the anonymous state $|\psi\rangle$ changes, the approximate state $\tilde{\phi}_i(\psi)$ must follow the $b = 1$ states $\phi'_i(\psi)$. Strictly, the condition is only that there exists a $\mathbf{V}$ such that the $P_c^A(\psi)$ given by (6) satisfies

$$P_c^A(\psi) \approx 1 \quad , \quad \forall \psi \in \mathcal{H}^B \quad (30)$$

where the ψ -dependence enters through $\phi_i(\psi)$ and $\phi'_i(\psi)$. The problem of impossibility (IP') becomes whether (30) holds when (25) is satisfied. A similar condition is obtained for Ψ that includes Babe's possible entanglement of the anonymous state in $\mathcal{H}^B$.

In the case of perfect security, the above use of anonymous states cannot prevent the success of EPR attacks due to

Theorem 3 [22]:

The condition

$$\rho_0^B(\psi) = \rho_1^B(\psi) \quad , \quad \forall \psi \in \mathcal{H}^B \quad (31)$$

implies, for every i ,

$$\tilde{\phi}_i(\psi) = \phi'_i(\psi) \quad , \quad \forall \psi \in \mathcal{H}^B \quad (32)$$

The proof is simple—by writing out (31) in terms of U_{bi} , it follows from theorem 8.2 of [23] on the freedom of CP-map decomposition that

$$\sqrt{p'_i} U_{1i} = \sum_j \sqrt{p_j} V_{ji} U_{0j} \quad (33)$$

for a unitary matrix $\mathbf{V}$. This operator relation guarantees that the state relation (32) is satisfied for all $|\psi\rangle$.

When (31) is satisfied and (18) is used to compute the cheating $U^A(\psi)$ according to Theorem 2, it is found to be independent of $|\psi\rangle$ and is given by the $\mathbf{V}$ of (33) due to the fact that the matrix $\langle \phi'_i | \phi_j \rangle$ becomes $\mathbf{V}$ multiplied by the inner product matrix $\langle \phi_i | \phi_j \rangle$ which is nonnegative. Indeed, the $\mathbf{V}$ in (33) is also determined by following the usual impossibility proof for any ψ . (Note that the Schmidt decomposition plays no role in the proofs of theorems 2 and 3 and in the results used in their proofs. Indeed, Jozsa's proof of Uhlmann's theorem in [18], which involves the Schmidt decomposition, can also be simplified along the line in the proof of Theorem 2 in Appendix A.) Theorem 3 is significant in that it shows it is operator, not state, entanglement that is needed in the presence of state randomness.

Under the condition

$$\rho_0^{BC}(\Psi) = \rho_1^{BC}(\Psi) \quad (34)$$

for one fixed $|\Psi\rangle$ of the form (24), one obtains similar to the proof of Theorem 3 that

$$\rho_0^B(\psi) = \rho_1^B(\psi) \quad \forall \psi \in \text{span}\{|\psi_k\rangle\}. \quad (35)$$

Equation (35) implies, in particular, that $\rho_0^B(\psi_k) = \rho_1^B(\psi_k)$ for each $|\psi_k\rangle$ and a fixed cheating transformation is available as above. The restriction on the validity of (35), and hence the possibility of Adam's successful cheating, to states in the subspace spanned by $\{|\psi_k\rangle\}$ is indispensable as shown in the example of Appendix B. We can summarize our two major

criticisms of the impossibility proof. First and foremost, it is not properly formulated so that under (34) or

$$\rho_0^{BC}(\Psi) \approx \rho_1^{BC}(\Psi) \quad (36)$$

for one fixed $|\Psi\rangle$ of (24), it may be Babe but not Adam who can cheat, either because she may sent $|\psi\rangle \notin \text{span}\{|\psi_k\rangle\}$, or there is a $\lambda_k \approx 0$ for which $\rho_0^B(\psi_k) \not\approx \rho_1^B(\psi_k)$. Secondly, even assuming $|\Psi\rangle$ is formed by Babe, there is no proof that there is any cheating transformation that would work for all $|\psi_k\rangle$.

Another way to formulate the problem at hand is to use CP-map or superoperator to characterize the transition from ψ to ρ_b^B , similar to the proof of Theorem 3. If two general CP-maps between operators on $\mathcal{H}_1$ and $\mathcal{H}_2$ are approximately equal in the sense of (25) with $\psi \in \mathcal{H}_1$, the question is what approximate relation would obtain between the positive operators in their respective decompositions. This question is a complicated one for application to our present problem, partly because when $\epsilon = \|\rho_0^B(\psi) - \rho_1^B(\psi)\|_1$ gets small, the security parameter n grows unbounded and the resulting $\mathcal{H}^B$ and ρ_b^B change profoundly. An infinite-dimensional nonseparable Hilbert space formulation of the problem appears necessary at the beginning. Until the question is settled in favor of impossibility, there is no general impossibility proof for protocols employing anonymous states even just in the simple fashion of (22).

The QBC formulation in this section, while more general than that of the impossibility proof which is a proper formulation only if the randomness in the protocol are all in (1)-(2), is still quite limited in scope. Indeed, the protocols of the following sections IV and V already do not fit into the present framework exactly. There are many other ways to introduce classical randomness in a protocol. Even though they can be represented quantum-mechanically, once measurements are made to pin them down they would function just as in a classical protocol, manifesting in the different ways the measurement results can be utilized. Just in the case of classical protocols, it does not appear possible to characterize all QBC protocols to a useful extent that something general can be said about the corresponding cheating probabilities. We will present elsewhere a general formulation of the QBC problem. It will be evident that the situation is far more intricate than the impossibility proof formulation (1)-(2).

IV Bit Commitment Scheme that Contradicts the Impossibility Proof

In this section, a protocol will be given that contradicts the quantitative claim of the impossibility proof, (IP) of (9) or (IP') of (8), without yet being unconditionally secure in the sense (US) of (8). Its extensions to unconditionally secure protocols will be given in the next section V. An intuitive description on how the QBC scheme may be developed is first provided to explain the underlying logic.

According to the impossibility proof formulation, there is a state $|\Phi_b\rangle$ of (1) - (2) shared by Adam and Babe. The most general attack by Adam after $|\Phi_0\rangle$ is committed is to apply a local U^A on $\mathcal{H}^A$ and then make a measurement on $\mathcal{H}^A$, or just to make a measurement on $\mathcal{H}^A$ as in (4)-(5), and opens $b = 1$. It is evident, from the way states in $\mathcal{H}^B$ can be affected this way as given by (5), that if $M = 1$ in (1) Adam cannot affect $\rho_0^B = |\phi\rangle\langle\phi|$ in $\mathcal{H}^B$ at all. Unconditional security is impossible in this case because $\bar{P}_c^B \sim \frac{1}{2}$ implies $|\langle\phi|\phi'\rangle| \sim 1$ and thus $\bar{P}_c^A \sim 1$ by simply announcing $b = 1$. If one lets $|\langle\phi|\phi'\rangle| \not\sim 1$ then Babe can cheat by measurement and the protocol is not concealing. Our protocols are to be developed from the following sequence of steps in general. To be specific, qubits will be used in this section.

To begin, let $|\phi\rangle$ and $|\phi'\rangle$ corresponding to $b = 0, 1$ be orthogonal so that Adam cannot cheat. To defeat Babe's cheating, Adam may send to Babe the information qubit among many random *decoy* states, named for example by their temporal order, and announce the information qubit position when he opens. To prevent Adam from the obvious cheating of sending in both $|\phi\rangle$ and $|\phi'\rangle$ and opening accordingly, an *anonymous* state $|\psi\rangle$ is first sent by Babe, with Adam generating $|\phi\rangle = U_0|\psi\rangle, |\phi'\rangle = U_1|\psi\rangle$ for $U_0 = I, U_1 = R(\theta, C)$ a rotation by an angle θ on some great circle C on the qubit Bloch-Poincare sphere. The rotation can be applied by Adam without knowing $|\psi\rangle$ assuming, as usual, that the orientations of all the qubit Bloch spheres are known to both Adam and Babe. Thus, $\langle\phi|\phi'\rangle = 0$ for $|\psi\rangle \in C$ and $\theta = \pi$. It can be intuitively expected that Babe cannot then determine b with $\bar{P}_c^B \sim \frac{1}{2}$ in the presence of sufficiently many decoy states. It should also be clear that Babe cannot improve his $\bar{P}_c^B$ by entanglement to $|\psi\rangle$, because she already chooses a $|\psi\rangle$ that allows her to make perfect discrimination if she knows which qubit is the one she sent, and so she has

no need to change $|\psi\rangle$ when she tries to cheat.

How about Adam's new possibilities of cheating at this stage? In all uses of anonymous states, the other party can always try to determine the state by measurement on the single copy. It is characteristics of quantum physics that the state cannot be determined and cannot be cloned [24]-[25] arbitrarily accurately, if it is drawn from a nonorthogonal set of states. However, Adam has a significant probability of success in such attempts, thereby such single use of qubit cannot yield an unconditionally secure protocol— $\bar{P}_c^B \sim \frac{1}{2}$ and $\bar{P}_c^A \not\sim 1$ but not $\bar{P}_c^A \sim 0$. More precisely, with n being the number of decoys states plus $|\psi\rangle$, one would have

$$\lim_n \bar{P}_c^B = \frac{1}{2}, \quad 0 < \lim_n \bar{P}_c^A < 1 \quad (37)$$

The protocol is thus concealing and quantitatively cheat-sensitive for Adam. If Adam indeed cannot do better than cloning, the impossibility proof is contradicted with (37) and thus is incorrect as a general proof.

A way to achieve (37), which has important practical significance, is for Babe to make verifying measurements on all the qubits before Adam opens. She would choose the basis corresponding to $\{|\psi\rangle, R(\pi, C)|\psi\rangle\}$ for all n qubits. Babe can evidently check whether Adam opens correctly in a perfect fashion when he identifies the qubit. It is intuitively clear, and will be explicitly proved below, that the protocol is concealing. By entangling to the qubit in state $|\psi\rangle$ in the form

$$\lambda_0 U_0 |\psi\rangle |e_0\rangle + \lambda_1 U_1 |\psi\rangle |e_1\rangle \quad (38)$$

Adam can find out Babe's measurement result but he cannot change it for cheating, as a matter of course—whatever operations and measurements he performs cannot affect the result Babe already obtained. A precise treatment of the above protocol QBCp3m, a preliminary (not yet unconditionally secure) protocol with Babe's measurement before opening, is detailed presently, to be followed by the security proof.

PROTOCOL QBCp3m

(i) Babe sends Adam a state $|\psi\rangle$ known only to herself, randomly picked from a fixed known great circle C on the Bloch sphere of the qubit $\mathcal{H}_2^B$.

(ii) Adam modulates $|\psi\rangle$ by $U_0 = I$ or $U_1 = R(\pi, C)$, rotation of $|\psi\rangle$ to its orthogonal state on C , for $b = 0$ or $b = 1$. He then picks $n - 1$ qubits with states independently and randomly chosen among all possible ones, and places the modulated qubit $\mathcal{H}_2^B$ randomly among them. He sends the n resulting qubits to Babe, each named by its position in the qubit sequence from 1 to n .

(iii) Babe measures $\{|\psi\rangle, R(\pi, C)|\psi\rangle\}$ on each qubit. Adam opens by revealing the position of $\mathcal{H}_2^B$ and the bit value. Babe verifies by checking her measurement result on $\mathcal{H}_2^B$.

We first show that this QBCp3m is concealing. For each possible i th position for $\mathcal{H}_2^B$ in the qubit sequence sent back by Adam, the state is of the form, in $\mathcal{H}^B$,

$$|\phi_1\rangle \cdots \cdots U_b|\psi\rangle \cdots |\phi_n\rangle \quad (39)$$

i

where each $|\phi_j\rangle, j \in \{1, \dots, n\}$ and $j \neq i$, is, say, one of the four BB84 states on C randomly and independently chosen. The index “ i ” underneath the state $U_b|\psi\rangle$ in (39) indicates that it occupies the i th position. Thus, the state to Babe is of the form, in $\mathcal{H}^B$

$$\rho_b^B = \frac{1}{n} \sum_i \frac{I}{2} \otimes \cdots \otimes \sigma_b \otimes \cdots \otimes \frac{I}{2}, \quad (40)$$

i

with $\sigma_b = U_b \sigma U_b^\dagger$ when Babe send a state σ to Adam without entanglement. Note that it is sufficiently for Adam to choose among two orthogonal states instead of all possible ones for each qubit, and for Babe to choose among four BB84 states instead of all in a great circle. While it should be clear that Babe gains nothing with entanglement, that situation will be dealt with later. From (40), one can evaluate $\bar{P}_c^B$ straightforwardly since $\rho_0^B - \rho_1^B$ is diagonal in the product basis that diagonalized $\sigma_0 - \sigma_1$ on each qubit. Let $n = 2\ell + 1$ and $\lambda_+ \leq 1$ be the positive eigenvalue of $\sigma_0 - \sigma_1$, it is shown in Appendix C that

$$\bar{P}_c^B - \frac{1}{2} = \frac{\lambda_+}{2^n} \begin{pmatrix} 2\ell \\ \ell \end{pmatrix} \quad (41)$$

The optimal probability (41) is obtained with $\lambda_+ = 1$ when the above product basis is measured and b is set to be 0 or 1 according to a majority vote on the positive and negative outcomes corresponding to the eigenvectors $|\lambda_+\rangle$ and $|\lambda_-\rangle$. From the standard bounds on binomial coefficients,

$$\frac{1}{4\sqrt{\ell}} < \bar{P}_c^B - \frac{1}{2} < \frac{1}{2\sqrt{\pi\ell}} \quad (42)$$

The optimal strategy is thus still concealing with $\lim_n \bar{P}_c^B = \frac{1}{2}$, but it is better than guessing at the qubit sent and then measure and decide on it alone, which yields $P_c^B = \frac{1}{2}(1 + 1/n)$.

To show that entanglement does not change the above situation in the simplest possible way, we would merely give a detailed proof that concealing is not affected by Babe's entanglement. When she entangles $\mathcal{H}_2^B$ to a $\mathcal{H}^C$ she would attach $\mathcal{H}^C$ to one of the qubits sent back by Adam. The resulting density operator is the same independently of which particular qubit position she attaches $\mathcal{H}^C$ to, from symmetry. From the triangle inequality for trace norm [18], the distance between the resulting $\bar{P}_b^B$ is bounded by

$$n \|\rho_0^B - \rho_1^B\|_1 \leq 2 + \|\bar{\rho}_0^B - \bar{\rho}_1^B\|_1 \quad (43)$$

where the term 2 is the maximum possible [23, App A] distance $\|\rho_0 - \rho_1\|_1$ for any states ρ_0 and ρ_1 , corresponding to the case where $\mathcal{H}^C$ is attached correctly to $\mathcal{H}_2^B$. The $\bar{\rho}_b^B$ are the same as (40) because the mismatched $\mathcal{H}^C$ state does not affect the trace distance as a consequence of

$$\|(\rho - \rho') \otimes \sigma\|_1 = \|\rho - \rho'\|_1 \quad (44)$$

Equation (44) follows immediately from evaluating the left-hand side in the diagonal representation of $(\rho - \rho') \otimes \sigma$. Thus, the protocol is still concealing from (42) and (43). Actually, it can be shown that the optimal $\bar{P}_c^B$ of (41) without entanglement remains optimal with entanglement. Note that our proof shows that the protocol is concealing for any $|\psi\rangle \in \mathcal{H}_2^B$ even though we may impose restriction on $|\psi\rangle$ in the binding proof or for ease of implementation.

Since Babe's verifying measurement can be perfectly made before Adam opens, a "no-clone" argument can be developed for binding. Adam cannot find out what measurement basis, not to mention $|\psi\rangle$, Babe used by entangling the qubits to $\mathcal{H}^A$ —the state on $\mathcal{H}^A$ is obtained by tracing over $\mathcal{H}^B$ and is independent, not only of $|\psi\rangle$, but of the specific

measurement basis Babe uses (or no measurement from her at all). Thus, he can gain no information from Babe's measurement to help him cheat in any way. One way for Adam to cheat is by cloning, as it is the same whether one wants to get $\{|\psi\rangle, |\psi\rangle\}$ or $\{|\psi\rangle, U|\psi\rangle\}$ for a known U . The optimal cloning performance is a fixed number $p_A < 1$ independent of n . The optimal one-to-two clone has been worked out for a variety of criteria and state sets. In the present situation, the state set is C or the four BB84 states. If the cloning is described by $|\psi\rangle \rightarrow |\psi_{ab}\rangle$ over two qubits with marginal states ρ_a and ρ_b , the criterion here corresponds to

$$F_c = \frac{1}{2} \langle \psi | \rho_a | \psi \rangle_{av} + \frac{1}{2} \langle \psi | U_1^\dagger \rho_b U_1 | \psi \rangle_{av} \quad (45)$$

with average over a uniform distribution on the state set from which $|\psi\rangle$ is drawn. It seems that the existing results [26]-[27] almost cover this case exactly [28]. Now, it appears that Adam cannot do better than this optimum by *any* action because if he could, he should have succeeded in cloning better than the optimal cloner, a contradiction, according to the following reasoning. He would have, by an objective physical procedure, succeeded in producing clones among n qubits, where he could identify which ones are the clones. If Babe did not measure first, this would not be surprising because the two copies are obtained on two different conditional (upon Adam's measurement result) states for Babe. The fact that Adam can identify both means that he could not just spread $n - 1$ qubit states uniformly on C , one of which would be close to $U|\psi\rangle$, but he wouldn't be able to tell which one. That he is not able to identify both simultaneously does not alter the fact he has cloned. Alternatively consider the following situation with the cloning of one copy of $|\psi\rangle \otimes |\psi\rangle$ into $\{|\psi\rangle \otimes |\psi\rangle, |\psi\rangle \otimes |\psi\rangle\}$, for a criterion as (41), with optimum $p_A < 1$. If Babe gets identical measurement results on two sets of n qubits sent back to her by Adam, each obtained by the same procedure as above, Adam would have succeeded in cloning $|\psi\rangle \otimes |\psi\rangle$ by carrying out the two different identification procedures on the two n -qubit sets and applying the results to both sets. To ensure that Babe could have the identical measurement results almost surely, consider the following Gedankenexperiment. Babe sends a large number N of identical states $|\psi\rangle$ to Adam, who carries out the same objective physical preparation (cheating) procedure on her N n -qubit sets. Babe performs her measurement on each and every set, obtaining,

with probability exponentially close to 1, pairs of identical results that total N' sets with N'/N close to 1 for sufficiently large N . Adam would then have, via the above separate identification procedure on each pair, succeeded in cloning in almost all of the original N sets. Both the above single-set argument and the present N -set argument are valid, but a complete formalization of the arguments will be given elsewhere.

Note that, in this protocol, Adam cannot cheat any better by generating decoy states other than $I/2$. Thus we have covered all possible actions by Adam and Babe, and can summarize the above results as

Theorem 4:

In protocol QBCp3m, Babe's optimal cheating probability can be made arbitrarily close to $\frac{1}{2}$ for large number of qubits n , while Adam's optimal cheating probability remains fixed and not arbitrarily close to 1.

What would happen to Adam's EPR attack in the above scheme if Babe performs her verifying measurement after he opens? One may have the protocol "QBC3" in reference [29] in which Babe disregards the $n - 1$ qubits not first sent by her. It is simpler to consider the following variant more in line with the impossibility proof formulation. Let $|\psi\rangle \in S = \{|1\rangle, |2\rangle, |3\rangle, |4\rangle\}$ where $|1\rangle$ and $|2\rangle$ are the vertical and horizontal states on C , and $|3\rangle$ and $|4\rangle$ are the two orthogonal diagonal ones, so together they make up the four standard BB84 states on C . Consider the case where each of the other $n - 1$ qubits sent by Adam has to be in $S' = \{|1\rangle, |2\rangle\}$. Adam modulates $|\psi\rangle$ by U_b and opens by identifying the $\mathcal{H}_2^B$ position and the states of all the qubits. Babe verifies by performing the corresponding projection measurements. Let $|\psi\rangle$ be purified as

$$\frac{1}{4} \sum_{\ell=1}^4 |\ell\rangle |f_\ell\rangle \quad (46)$$

for $|\ell\rangle \in S \subset \mathcal{H}_2^B$ and orthonormal $|f_\ell\rangle \in \mathcal{H}^C$. Let $U_{1j}, j \in \{2, \dots, n\}$ be the unitary operator that swaps qubit position 1 and j on $\mathcal{H}^B = \mathcal{H}_2^B \otimes_{j=2}^n \mathcal{H}_2^j$. On $\mathcal{H}^A \otimes \mathcal{H}^B$, Adam can form the entanglement by employing orthonormal $|e_i\rangle \in \mathcal{H}^A, i \in \{1, \dots, n \cdot 4^{n-1}\}$, with uniform or whatever probabilities, using U_{1j} and S' . In analogy with QBCp3m, we have a preliminary

protocol QBC p3u which is close to a usual one in which Adam can launch EPR attacks.

PROTOCOL QBCp3u

(i) Babe sends Adam a state $|\psi\rangle$ known only to herself, randomly picked from the four BB84 states on a fixed great circle C of the qubit $\mathcal{H}_2^B$.

(ii) Adam modulates $|\psi\rangle$ by $U_0 = I$ or $U_1 = R(\pi, C)$ for $b = 0$ or 1 . He then picks $n - 1$ qubits with states independently and randomly from two orthogonal states known to Babe, places the modulated qubit $\mathcal{H}_2^B$ randomly among them, and sends the n qubits to Babe in a named order.

(iii) Adam opens by revealing the state of all the qubits and identifying $\mathcal{H}_2^B$. Babe verifies by checking the corresponding projections.

This protocol is concealing exactly as in QBCp3m. As shown in section III, the impossibility proof does not cover this protocol. Indeed, assuming Adam opens perfectly for $b = 0$ as in the impossibility proof, it can be shown that he cannot then cheat with $\bar{P}_c^A \sim 1$. The basic reason is that he can only identify correctly on the decoy states, for arbitrary $|\psi\rangle$, by not involving $|\psi\rangle$ in the entanglement of the decoy states. However, he cannot then rotate $|\psi\rangle$ to its orthogonal complement on C . The full security proof covering the situation in which Adam does not open perfectly is being developed.

V Unconditionally Secure Bit Commitment Schemes

The QBC protocol in the previous section that invalidates the impossibility proof can be extended to fully unconditionally secure protocols as described in the following. This may be expected because if Adam cannot cheat nearly perfectly on one qubit, his cheating probability can be brought exponentially close to zero in a sequence of independent qubits. To extend the above protocols in this manner, first consider the case where $\mathcal{H}_2^B$ in QBCp3m is replaced by $\bar{\mathcal{H}}^B = \otimes_{k=1}^m \mathcal{H}_{2k}^B$. Let Babe send Adam a sequence of m qubits

$$|\psi\rangle = |\psi^1\rangle \otimes \cdots \otimes |\psi^j\rangle \cdots \otimes |\psi^m\rangle, \quad j \in \{1, \dots, m\} \quad (47)$$

Each $|\psi^j\rangle$ is randomly and independently chosen from the same fixed great circle C for all the m qubits, and named by its sequence position j within $\bar{\mathcal{H}}^B$. Adam applies U_b to each of these qubits and then randomly places $\bar{\mathcal{H}}^B$ among a sequence of $N - 1$ quantum spaces $\mathcal{H}_\ell^B$, each a product of m qubits, with states on all the $m(N - 1)$ qubits randomly and independent chosen from a fixed great circle C' . The total sequence or product state

$$|\chi_1\rangle \cdots |\chi_\ell\rangle \cdots |\chi_N\rangle, \quad \ell \in \{1, \dots, N\} \quad (48)$$

is re-named by the new position ℓ and sent back to Babe. Apart from the modulated state in $\bar{\mathcal{H}}^B$, each of the other $N - 1$ $|\chi_\ell\rangle$ in $\mathcal{H}_\ell^B$ is a product of m qubit states. Each of the N state spaces would be referred to as a *qumode*. Similar to (35), Adam knows, but Babe does not, which $|\chi_\ell\rangle$ is the modulated $|\psi\rangle$, and he opens by giving Babe this information, but he does not know what the $|\psi^j\rangle$'s are. Before Adam opens, Babe measures on every qumode the product qubit basis given by $\{|\psi^j\rangle, R(\pi, C)|\psi^j\rangle\}$ across the m qubits, which diagonalizes $\rho_0^B - \rho_1^B$. She optimally decides on b by the majority of the two patterns of $|\psi^j\rangle$ and $R(\pi, C)|\psi^j\rangle$, the other patterns occurring with equal probability.

To prove concealing, the following argument is used in lieu of evaluating directly the trace distance. For any fixed m , let N be chosen large enough that the number of times a particular pattern of $|\psi^j\rangle$ in (47) shows up in Babe's measurement on a random qumode is at least $(N - 1)(2^{-m} - \delta)$ for a small $\delta > 0$, where $(N - 1)2^{-m}$ is the average. This is possible with a probability exponentially close to 1 from the Chernov bound. The situation

then becomes the same as the qubit case of section IV, with n replaced by $N(2^m - \delta)$ for the upper bound in (42), which can then be set to any desired small level by further increasing N . Babe's possible entanglement can be handled as in (43). Thus, the protocol is concealing. Adam's optimal cheating probability is given by $\bar{P}_c^A = p_A^m$, which fixes m for given $\bar{P}_c^A < \epsilon$. We summarize the results.

PROTOCOL QBC3m1

(i) Babe sends Adam a product state (47), each $|\psi^j\rangle$ named by its position and independently and randomly chosen from a BB84 state set S in C .

(i) Adam modulates each and all $|\psi^j\rangle$ by $U_0 = I$ or $U_1 = R(\pi, C)$, then independently and randomly place the exact sequence among $N - 1$ qumodes, each a product of m qubits randomly distributed on S . He sends the N qumodes to Babe in a named order.

(iii) Babe measures the m $\{|\psi^j\rangle, R(\pi, C)|\psi^j\rangle\}$ on each of the N qumodes. Adam opens by announcing which qumode is the modulated $|\psi\rangle$ and the bit value. Babe verifies by checking her measurement result.

Theorem 5:

Protocol QBC3m1 is unconditionally secure.

Variations of the protocol can be easily created without affecting the unconditional security. For example, consider the case where Babe sends (47) to Adam which he returns in m segments of N qubits each, the j th one containing exactly one $|\psi^j\rangle$ from (47). Babe can then make a uniform measurement on each N -sequence, deciding whether each such N -sequence corresponds to a 0 or 1 by a majority vote, and the overall b by a majority vote on the m outcomes.

To show that such a protocol is concealing, one may first take care of Babe's entanglement possibility to $\mathcal{H}^C$ by, similar to (43),

$$\|\rho_0^B - \rho_1^B\|_1 \leq [1 - p(N, m)] \cdot 2 + p(N, m) \cdot \|\bar{\rho}_0^B - \bar{\rho}_1^B\|_1 \quad (49)$$

where $p(N, m) = (1 - \frac{1}{N})^m$ is the probability that none of the m attached entangled qubits in $\mathcal{H}^C$ matches the actual qubit position, which can be made arbitrarily close to 1 for any fixed

m by making N large. Then one argues that independent qubit probability distributions are obtained because for optimal P_c^B Babe should not entangle across the qubits in (47) as that would create additional randomness for the individual qubit measurements she would make, the latter needed since she has a vanishingly small probability to locate her own qubits. (Indeed, there is no point for her to correlate the $|\psi^j\rangle$ in the first place, as an involved classical probabilistic argument would show.) From the independence of $|\chi_\ell\rangle$ and the $|\psi^j\rangle$ positions in the m N -sequences, the optimal decision Babe can make is to decide on 0 or 1 on each of the N -sequences as the $m = 1$ case, and then take a majority vote to decide on b . Let p be the probability of Babe's correct decision in each N -sequence. Then p is given by (41) and bounded as in (42) with n replaced by N . The overall $\bar{P}_c^B = \sum_{k=0}^{(m-1)/2} \binom{m}{k} p^k (1-p)^{m-k}$ can be made, for any fixed m , arbitrarily close to $1/2$ by making p arbitrarily close to $1/2$, i.e., with N sufficiently large, because this $\bar{P}_c^B$ is a continuous function of p . The value of m is determined from $p_A^m < \epsilon$ from cloning. With $\bar{P}_c^B - \frac{1}{2} < \epsilon$, the unconditional security proof is completed for the following

PROTOCOL QBC3m2

(i) Babe sends Adam a sequence of m qubits, each $|\psi^j\rangle$ named by its position and independently and randomly chosen from a great circle C .

(ii) Adam modulates each and all $|\psi^j\rangle$ by $U_0 = I$ and $U_1 = R(\pi, C)$, then places each $U_b|\psi^j\rangle$ independently and randomly among the j th of m succeeding N -sequences of qubits, the states of all the other qubits independently and randomly chosen. He sends the $n = mN$ succeeding qubits with their position names to Babe.

(iii) Babe measures $\{|\psi^j\rangle, R(\pi, C)|\psi^j\rangle\}$ on the N qubits of the j th sequence for all j . Adam opens by revealing the positions of $U_b|\psi^j\rangle$ and the bit value. Babe verifies by checking her measurement results on these qubits.

Theorem 6:

Protocol QBC3m2 is unconditionally secure.

Protocols QBC3u1 and QBC3u2 can be introduced similar to the last section. They are

omitted here since their full security proofs are not yet available.

VI Conclusion

In this paper we have explicitly detailed two major ways in which the QBC impossibility proof fails as a general proof. There are two corresponding significant general issues concerning the impossibility proof. One is that classical randomness and the corresponding information flow between the two parties may play a significant role in a general protocol. Such a role has not been completely characterized for the classical case, and cannot be simply eliminated by quantum purification. This points to the more general, second issue: how one can characterize all possible QBC protocols at all when one has not been able to do that for any type of classical cryptographic protocols. In particular, there are many possible protocols with random numbers generated by Adam and Babe during various stages of a protocol, necessitating uniformity conditions similar to (25) that would intertwine in a complicated classical way that is not resolved by quantum purification. As things stand, it is even open whether a perfectly secure QBC protocol is possible, given the limited scope of Theorem 3.

In any event, it is possible to have unconditionally secure quantum bit commitments, as protocols QBC3m1 and QBC3m2 demonstrate. Equally significantly, these protocols can be carried out without any quantum memory to be used between commitment and opening. In applications to key management or identification/authentication, such required quantum memory would be very long on microscopic scale, at least for network type situations. It is unrealistic to expect that such quantum memory would become available in any reasonable amount of time. Thus, these protocols represent a major step in advancing the possible practical use of quantum bit commitment. Moreover, each qubit in the protocol can be replaced by a full optical field mode and qubit state by large-energy coherent state, without affecting the essential underlying operations, thus making the protocol even easier to implement. A full description of such protocols and quantitative tradeoffs between security and complexity will be given in a future paper.

Acknowledgment

I would like to thank M. D'Ariano and M. Ozawa for useful discussions.

This work was supported in part by the Defense Advanced Research Project Agency and in part by the Army Research Office.

Appendix A

Proof of Theorem 2

By choosing $|e_i\rangle = |e'_1\rangle$ in (1)-(2), one obtains

$$|\langle\Phi_1|U^A|\Phi_0\rangle| = |tr\mathbf{U}\mathbf{\Lambda}| \quad (\text{A1})$$

The maximum of $|tr\mathbf{U}\mathbf{\Lambda}|$ over all unitary $\mathbf{U}$ is attained when $\mathbf{U}\mathbf{\Lambda}$ is nonnegative definite with maximum value given by $tr|\mathbf{\Lambda}|$ [17, p.43]. Thus $\mathbf{U}$ is determined by the polar decomposition (generalization to infinite dimensional space can be obtained via maximal partial isometry) of $\mathbf{\Lambda} = |\mathbf{\Lambda}|\mathbf{U}^\dagger$.

With $p_i = p'_i$, $\bar{P}_c^A$ is given by (20) and is thus bounded above by $\sum_i |\mathbf{\Lambda}|_{ii}$ which is just $tr|\mathbf{\Lambda}| = F$. For a set of probabilities α_i and complex numbers λ_i , one has

$$\sum_i \alpha_i |\lambda_i|^2 \geq |\sum_i \alpha_i \lambda_i|^2 \quad (\text{A2})$$

as a consequence of Jensen's inequality and the concavity of the function $x \mapsto x^2$. The lower bound of (21) follows from (A2) with $\alpha_i = p_i$ and $\lambda_i = \sqrt{\tilde{p}_i/p_i} \langle \tilde{\phi}_i | \phi'_i \rangle$, valid for $p_i \neq p'_i$.

Appendix B

Example on Proper Concealing

In the notations of sections II-III, the following example shows that for (24), even with no small λ_k , the condition (34) does not imply that Adam can cheat as claimed by the impossibility proof.

Consider 2-qubit $\mathcal{H}^B = \mathcal{H}_2 \otimes \mathcal{H}_2$ and $|\Psi\rangle \in \mathcal{H}^B \otimes \mathcal{H}^C$ given by

$$|\Psi\rangle = \frac{1}{\sqrt{2}}(|a\rangle|a'\rangle|f_1\rangle + |a'\rangle|a\rangle|f_2\rangle) \quad (\text{B1})$$

where $|a\rangle$ and $|a'\rangle$ are two openly known orthogonal states in $\mathcal{H}_2$, and $|f_i\rangle$ are orthonormal in $\mathcal{H}^C$, which is also a qubit. The operations are taken to be $p_1 = p'_1 = p_2 = p'_2 = \frac{1}{2}$, $U_{01} = I$, $U_{02} = P$ the permutation operator switching the two qubit positions in $\mathcal{H}^B$, $U_{11} = R$ a rotation that brings $|a\rangle$ to $|a'\rangle$ and $|a'\rangle$ to $|a\rangle$, $U_{12} = RP$. It follows easily that, after entanglement by Adam, $\rho_0^{BC}(\Psi) = \rho_1^{BC}(\Psi)$ and he can cheat perfectly when Babe forms (B1).

However, it is Babe who can actually cheat perfectly in this situation. Instead of sending (B1) she can send $|a\rangle|a\rangle \in \mathcal{H}^B$ instead, which would defeat Adam's cheating and allows herself to cheat. The underlying reason is, of course, that (31) or (25) is not satisfied, and $|a\rangle|a\rangle \notin \text{span}\{|a\rangle|a'\rangle, |a'\rangle|a\rangle\}$, violating the condition required for (34)-(35). Clearly, there is no reason why Babe wants to be honest so Adam can cheat. Thus, the impossibility proof formulation, which does not have a condition such as (36), is not a meaningful one in the presence of random numbers, with consequent incorrect claim on same situation.

Appendix C

Evaluation of Trace Distance

One straightforward way to evaluate $\|\rho_0^B - \rho_1^B\|_1$ for ρ_b of (40) is to directly compute the trace norm in the product basis spanned by $\{|\lambda+\rangle, |\lambda-\rangle\}$ for each qubit. Let k be the number of $|\lambda-\rangle$ in a product-basis vector. One has, from a direct counting calculation,

$$\|\rho_0^B - \rho_1^B\|_1 = \frac{\lambda_+}{n2^{n-1}} \sum_{k=0}^n \binom{n}{k} |n - 2k| \quad (\text{C1})$$

The binomial sum in (C1) can be evaluated in closed form. With $n = 2\ell + 1$,

$$\sum_{k=0}^n \binom{n}{k} |n - 2k| = 2(2\ell + 1) \binom{2\ell}{\ell} \quad (\text{C2})$$

Equation (41) follows from (C1)-(C2).

Appendix D

Simple Summary of Protocols QBCp3m, etc.

The statement, underlying logic, and security of protocol QBCp3m can be simply presented as follows. The detailed proofs are given in the paper.

Let Babe send Adam a qubit in state $|\psi\rangle$ known only to herself, $|\psi\rangle \in C \subset \mathcal{H}_2^B$ in a fixed great circle C of the qubit Bloch sphere. Depending on $b = 0$ or 1 , Adam leaves it alone or rotates it to its orthogonal state $|\psi'\rangle$, then sends it back to Babe among a number $n-1$ of random decoy qubit states. Independently of b , Babe can make the same qubit measurement of the basis $\{|\psi\rangle, |\psi'\rangle\}$ on every of the n qubits before Adam opens. The protocol is still concealing with $\bar{P}_c^B \rightarrow \frac{1}{2}$ as $n \rightarrow \infty$, because she does not know which qubit is the one she sent. It is clear that Babe cannot determine b any better by sending $|\psi\rangle \notin C$ or by entangling $|\psi\rangle$. Because Adam cannot gain any information on Babe's measurement basis via entanglement, his optimal cheating probability $\bar{P}_c^A$ is given by an appropriate one-to-two clone fidelity p_A , which is independent of n and not arbitrarily close to 1. As he has to open 0 and 1 on two different qubits given Babe already measures, the optimality of p_A would be contradicted if he can do any better. Thus far, the quantitative claim of the impossibility proof, (IP) of (9) or (IP') of (10), has been invalidated by the above protocol QBCp3m. More significantly, it shows that the impossibility proof formulation misses a whole class of protocols in which Babe can make the verifying measurement independently of b before Adam opens.

It is straightforward to extend QBCp3m to unconditionally secure protocols, such as QBC3m1 and QBC3m2, by having Babe send Adam a sequence of m independent $|\psi_i\rangle$'s with p_A^m set to any arbitrarily small value ϵ . Adam sends back each of the m uniformly modulated qubits in different restricted ways among n qubits. Babe makes the corresponding measurements before Adam opens. The resulting protocols are concealing with n sufficiently large for any fixed m , which is determined by Adams optimal cheating probability $\bar{P}_c^A = p_A^m$, and are thus fully unconditionally secure in the sense (US) of (8).

References

- [1] C.H. Bennett, G. Brassard, and A.K. Ekert, Sci. Am. (Int. Ed.) **267** (10), 50 (1992).
- [2] A review is given by G. Brassard and C. Crépeau, SIGACT news **27** No. 3, 13 (1996).
- [3] D. Mayers, LANL quant-ph/9603015.
- [4] D. Mayers, Phys. Rev. Lett. **78**, 3414 (1997).
- [5] H.K. Lo and H.F. Chau, Phys. Rev. Lett. **78**, 3410 (1997).
- [6] H.K. Lo and H.F. Chau, LANL quant-ph/9709053.
- [7] H.K. Lo and H.F. Chau, LANL quant-ph/9711065; Physica D **120**, 177 (1998).
- [8] H.K. Lo, Phys. Rev. A **56** 1154 (1997).
- [9] G. Brassard, C. Crépeau, D. Mayers, and L. Salvail, LANL quant-ph/9712023.
- [10] G. Brassard, C. Crépeau, D. Mayers, and L. Salvail, LANL quant-ph/9806031.
- [11] A. Kent, Phys. Rev. Lett. **83**, 1447 (1999); LANL quant-ph/9906103.
- [12] L. Hardy and A. Kent, LANL quant-ph/9911043.
- [13] The standard reference is the Appendix of L.P. Hughston, R. Jozsa and W.K. Wootters, Phys. Lett. A **183**, 14 (1993). It is called the “normal form” of a pure state in $\mathcal{H}^A \otimes \mathcal{H}^B$ by J.M. Jauch, *Foundations of Quantum Mechanics*, Addison-Wesley, 1968, p. 182.
- [14] H.P. Yuen, LANL quant-ph/0009113; also in *Quantum Communication, Computation, and Measurement 3*, ed. by P. Tombesi and O. Hirota, Plenum, New York, 2001, p. 285.
- [15] J. Mueller-Quade and H. Imai, LANL quant-ph/0010112.
- [16] C.W. Helstrom, *Quantum Detection and Estimation Theory*, Academic Press, 1976, Ch. IV.
- [17] R. Schatten, *Norm Ideals of Completely Continuous Operators*, Springer, 1970, Ch. III.

- [18] R. Jozsa, J. Mod. Opt. A **1**, 2315 (1994).
- [19] C.A. Fuchs and J. van de Graaf, IEEE Trans. Inform. Theory **45**, 1216 (1999).
- [20] D. Gottesman and H.K. Lo, Physics Today, Nov 2000, p. 22.
- [21] Adam does not have to use the agreed upon p_i and p'_i either. However, it is to his advantage to do so in the standard formulation, because the protocol is then concealing but he can still cheat.
- [22] Theorems 2 and 3 were first presented at the QUICK meeting in Corsica, France, April, 2001.
- [23] M.A. Nielsen and I.L. Chuang, *Quantum Computation and Quantum Information*, Cambridge Univ. Press, 2000.
- [24] W.K. Wootters and W.H. Zurek, Nature **299**, 802 (1982).
- [25] H.P. Yuen, Phys. Lett. **113A**, 405 (1986).
- [26] M. Keyl and R.F. Werner, J.Math.Phys. **40**, 3283 (1999).
- [27] G. M. D'Ariano and P. L. Presti, LANL quant-ph/0101100.
- [28] G. M. D'Ariano has been able to show that $F_c = \frac{1}{2} \left(1 + \frac{1}{\sqrt{2}}\right)$ for the criterion (39) when $|\psi\rangle$ is drawn either from a great circle or from the four BB84 states on a great circle. (private communications).
- [29] H.P. Yuen, LANL quant-ph/0106001.